

# Bodycoat Accelerator

## PRODUCT DESCRIPTION

Bodycoat Accelerator is a single component catalyst, used to speed up the set time of the bodycoat. Ideally used for applications occurring in cool weather conditions.

## CHARACTERISTICS

- East to use
- Accelerates bodycoat setting
- Facilitates application in cold weather (40-50°F /4-10°C)

## CAUTIONS & LIMITATIONS

- For use in temperatures 40-50°F (4-10°C) only.
- Use only one packet per bag of bodycoat

## COLOR

White powder

## PACKAGING

1 ounce (28g) bag

## MIXING

Use one packet per 50 lb bag of bodycoat.

Bodycoat Accelerator should be thoroughly mixed into the bodycoat material immediately after the normal mixing process using a mechanical mixer at slow speeds until a homogeneous mixture is obtained. Be sure to incorporate material on the sides and bottom of the mixing container to avoid lumps. Cure time will vary based on atmospheric conditions.

## FIRST AID

### EYE CONTACT

Flush eye with water for at least 15 minutes. Get medical attention promptly.

### INHALATION

Remove to fresh air. If not breathing, give artificial respiration. If having difficulty breathing, give oxygen. Get immediate medical attention.

### SKIN CONTACT

Wash affected area thoroughly with soap and water. Remove contaminated cloths and laundry before reuse.

### INGESTION

Do not induce vomiting. Get medical attention immediately.

### FIRE

Wear self-contained breathing apparatus with full face piece and protective clothing. Use foam, carbon dioxide, dry chemical, and/or halogenated agents.

### SPILL

For dry material, collect by sweeping and scooping. Transfer collected material to a container, being careful to minimize creation of dust. For wet material, scoop material up and transfer to an open container. Allow material to dry before disposal. Keep spilled products out of sewers, streams, and water systems.

## STORAGE & HANDLING

Store Accelerator at temperatures between 40°F and 100°F (4°C and 38°C). Do not store at high temperatures or in direct sunlight. Keep packets dry. Promptly clean tools and equipment with water and mild detergent. Always wear proper safety equipment, including particle mask, eye protection, and gloves when mixing and/or applying these products.

## TECHNICAL DATA

Solids by Weight .....	100%
Solids by Volume .....	100%

## SHELF LIFE

The shelf life is one (1) year from the date of manufacture in the original, unopened container when properly stored.

## WARRANTY

Limited manufacturer's defect warranty. Contact Mer-Ko Technical Service Department for specific warranty information or [www.parexmer-ko.com](http://www.parexmer-ko.com)

# Product Data Sheet

---

## Bodycoat Accelerator

*Any recommendation or suggestion relating to the use of MER-KO products made via current technical literature, marketing materials, technical application guides, specifications, and the like, or in response to specific inquiry or otherwise, is based on data believed to be reliable. However, the products and information are intended for use by Buyers having requisite skill and know-how in the industry. Therefore, it is the responsibility of the Buyer to satisfy the necessary requirements of suitability of the products for its own particular use, and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results. Mer-Ko believes the information contained herein is true and accurate as of the date of publication. Information contained here is for evaluation only. Mer-Ko reserves the right to modify and/or change products or literature at any time and without prior notice.*



**Corporate Office**  
ParexLahabra, Inc.  
4125 E. La Palma Avenue, Suite 250  
Anaheim, CA 92807

(714) 778-2266  
(866) 516-0061  
infomer-ko@parexlahabra.com  
www.parexmer-ko.com



MEMBER OF

