

# Mer-Ko Clear Seal WBA

**PRODUCT DESCRIPTION**

Mer-Ko Clear Seal WBA is designed to resist direct exposure to environmental elements and withstand normal wear. It is a clear acrylic emulsion sealer which is applied as a milky white liquid and dries clear. Mer-Ko's Clear Seal WBA will seal the surface protecting it from water and salt penetration. It makes it easier to remove dirt and other debris from the surface when it is cleaned. When traffic patterns become visible or heavy impacts mar the surface. Clear Seal WBA should be re-applied to restore the aesthetic appeal. Surfaces should be re-sealed every 2 years for best results, or per the schedule listed on the warranty issued.

**CHARACTERISTICS**

- Easy Application and water clean-up
- Enhances the beauty of cementitious surfaces
- Improved stain resistance
- Will not soften under high temperatures
- Resists degradation from UV, ozone, and weathering
- Outstanding long-term durability and performance
- Excellent chemical resistance

**CAUTIONS & LIMITATIONS**

- The substrate surface must be structurally sound, clean, dry and free of dirt, dust, oil, grease, paint or other contaminants at the time of material application.
- Do not apply when temperature may drop below 40°F (4°C) or rise above 100°F (38°C).
- Do not apply in damp weather or when rain is expected within 24 hours.
- Do not allow to Clear Seal WBA to freeze or be exposed to high temperatures.

**COLOR**

Milky white in liquid state, dries clear.

**PACKAGING**

5 gallon (18.9 liter) pail

**MIXING**

After opening the container, gently stir until uniform in color.

**APPLICATION**

Sweep the entire deck surface clean of any residual dust or debris. Spray or roller apply one coat of Mer-Ko's Clear Seal WBA. Allow to dry for a minimum of 1 hour. Then, proceed with a second application in the same manner as the first. Allow a 2 hour cure before introducing light foot traffic; 24 hours before returning to full service.

**FIRST AID**

**EYE CONTACT**

Flush eye with water for at least 15 minutes. Get medical attention promptly.

**INHALATION**

Remove to fresh air. If not breathing, give artificial respiration. If having difficulty breathing, give oxygen. Get immediate medical attention.

**SKIN CONTACT**

Wash affected area thoroughly with soap and water. Remove contaminated cloths and laundry before reuse.

**INGESTION**

Do not induce vomiting. Get medical attention immediately.

**TECHNICAL DATA**

Coverage rates are approximate only and can vary greatly due to surface conditions, humidity, temperature and installation techniques.

|                                  |   |
|----------------------------------|---|
| <b>New surfaces</b> .....        | 1,200-1,600 ft <sup>2</sup> (111-148 m <sup>2</sup> )/5 gallon pail |
| <b>Old porous surfaces</b> ..... | 400-1,000 ft <sup>2</sup> (37.2-92.3 m <sup>2</sup> )/5 gallon pail |
| <b>Freezing Point</b> .....      | 32°F  |
| <b>Stain Resistance</b> .....    | Excellent to most stains  |
| <b>Chemical Resistance</b> ..... | Excellent to most acids and alkali                                  |
| <b>Solids by Volume</b> .....    | 30%   |
| <b>Dry Time</b> .....            | 1 hr minimum at 70°F (21°C) 50% RH                                  |
| <b>VOC</b> .....                 | Less than 75 g/L (ASTM D3960)                                       |
| <b>Weight per Gallon</b> .....   | 8.81 lbs/gallon (ASTM C109)   |

**FIRE**

Wear self-contained breathing apparatus with full face piece and protective clothing. Use foam, carbon dioxide, dry chemical, and/or halogenated agents.

**SPILL**

Scoop material up and transfer to an open container. Allow material to dry before disposal. Keep spilled products out of sewers, streams, and water systems.

**HANDLING & STORAGE**

Store Clear Seal WBA out of direct sunlight at temperatures between 50°F and 100°F (10°C and 38°C). Do not allow to freeze. Promptly clean tools and equipment with water and mild detergent. Always wear proper safety equipment, including eye protection, and gloves when mixing and/or applying these products.

**SHELF LIFE**

The shelf life is one (1) year from the date of manufacture in the original, unopened container when properly stored.

**WARRANTY**

Limited manufacturer's defect warranty. Contact Mer-Ko Technical Service Department for specific warranty information or [www.parexmer-ko.com](http://www.parexmer-ko.com)

# Product Data Sheet

---

## Mer-Ko Clear Seal WBA

*Any recommendation or suggestion relating to the use of MER-KO products made via current technical literature, marketing materials, technical application guides, specifications, and the like, or in response to specific inquiry or otherwise, is based on data believed to be reliable. However, the products and information are intended for use by Buyers having requisite skill and know-how in the industry. Therefore, it is the responsibility of the Buyer to satisfy the necessary requirements of suitability of the products for its own particular use, and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results. Mer-Ko believes the information contained herein is true and accurate as of the date of publication. Information contained here is for evaluation only. Mer-Ko reserves the right to modify and/or change products or literature at any time and without prior notice.*

**MER-KO**<sup>®</sup>  
**PAREX**  
[www.parexmer-ko.com](http://www.parexmer-ko.com)

### Corporate Office

Parex USA, Inc.  
4125 E. La Palma Ave., Suite 250  
Anaheim, CA 92807  
(866) 516-0061  
Tech Support: (800) 226-2424

